

ECLAZ

SOURCE OF LIGHT AND WELLBEING

An essential function of glass is the transparency and thus the possibility to use the daylight. This offers no second building material in this kind. The ECLAZ family, consisting of ECLAZ and ECLAZ ONE fulfils the requirement for maximum daylight transmission (high TL), and efficient use of solar energy (high solar factor) like no other. Also, the unique coating technology allows the blue components of the light spectrum to pass through the glass more intensely, allowing ECLAZ to truly offer more daylight.

The to be tempered variants ECLAZ II and ECLAZ ONE II also offer higher mechanical and thermal resistance. As standard, we offer the coated glasses in 4 and 6 mm thickness and maximum dimensions of 6 m \times 3.21 m; further glass thicknesses and dimensions are available on request.

If a to be tempered product has to be mixed with a product that cannot be tempered, as well as in façade applications in general we recommend prior sampling.

AESTHETICS

Type/Color

The low external reflection and the colour-neutral exterior produce a successful combination of function and aesthetics. Wherever more daylight is desired inside the room, ECLAZ is the first choice. The glass of the ECLAZ family is also suitable for the renovation of listed buildings.

ECLAZ ONE and ECLAZ ONE II

VISUAL COMFORT

Extremely translparent, even in triple glazing and an extremely high colour rendering: for a bright internal atmosphere and an equally brilliant view to the outside.

INDOOR COMFORT

Ua-Value*

Highly efficient and optimal thermal insulation: which maximises the sun's heat, lowering a building's energy usage.

THERMAL INSULATION

Perfectly insulates the interior and thus minimises central heating costs.

COMBINATIONS

Light transmission TI** Solar factor** ex reflection** in reflection**

47

SECURIT (toughened safety glass), STADIP (laminated glass), STADIP SILENCE (sound insulation) and STADIP PROTECT (injury and burglary protection)

21/23***

1,00,00101	[W/m ² K]	[%]	[%]	[%]	[%]
Standard composition CLIMAPLUS 4 16	4 - coating on	oos. 3 on PLANICLEAR,	90% Argon		
ECLAZ and ECLAZ II	1,1	83	71	12	11
ECLAZ ONE and ECLAZ ONE II	1,0	80/79***	60	15/16***	16/18***
Standard composition CLIMATOP 4 12 4	1 12 4 - coating o	on pos. 2 and 5 on PLAN	NICLEAR, 90%	Argon	
ECLAZ and ECLAZ II	0.7	77/76***	60/59***	1//	1/1

^{*}according to EN 673 **according to EN410 ***Values may differ for toughened (II) and non-toughened coatings with the same glass compositions.

70/69***

